

Model # 526DX Specifications	
Engine Power:	26 HP
Engine Manufacturer:	Perkins
Engine Description:	403C11 Diesel
Tip Capacity:	2100 LBS
Hydraulic pressure:	3000 PSI
Dump Height:	60 "
Travel speed:	3.7 MPH
Ground clearance:	5 "
Ground pressure:	3.1 PSI
Overall Length (without bucket):	77 "
Operating Capacity, 35% of tip load:	735 LBS
Operating Capacity, 50% of tip load:	1050 LBS
Hydraulic Auxiliary Flow:	14.5 GPM
Overall Width (fully extended):	43.5 "
Overall Operating Height (Fully Raised):	98 "
Weight (without bucket):	2410 LBS
Hinge pin height (fully raised):	76 "
Track Width:	9 "

Model # 530X Specifications	
Engine Power:	30 HP
Engine Manufacturer:	Kohler
Engine Description:	Command Pro Gas
Tip Capacity:	1650 LBS
Hydraulic pressure:	3000 PSI
Dump Height:	60 "
Travel speed:	3.7 MPH
Ground clearance:	5 "
Ground pressure:	3.1 PSI
Overall Length (without bucket):	77 "
Operating Capacity, 35% of tip load:	577.5 LBS
Operating Capacity, 50% of tip load:	825 LBS
Hydraulic Auxiliary Flow:	14.5 GPM
Overall Width (fully extended):	43.5 "
Overall Operating Height (Fully Raised):	98 "
Weight (without bucket):	2200 LBS
Hinge pin height (fully raised):	76 "
Track Width:	9 "

Model # 532DX Specifications	
Engine Power:	32 HP
Engine Manufacturer:	Kubota
Engine Description:	D1105T
Width Variable Track (min):	35 "
Width Variable Track (max):	43.5 "
Weight:	2,470 LBS
Tip Capacity:	2,100 LBS
Hydraulic pressure:	3,000 PSI
Hydraulic flow:	14.5 GPM
Hydraulic tank capacity:	24 GAL
Dump Height:	60 "
Hinge pin height:	76 "
Travel speed:	3 MPH
Fuel tank capacity:	9 GAL
Ground clearance:	5 "
Ground pressure:	3.7 PSI
Overall Length (without bucket):	77 "
Operating Capacity, 50% of tip load:	1,050 LBS
Overall Operating Height (Fully Raised):	98 "